

# ALCATEL-LUCENT 8340 SMART IP-DECT ACCESS POINTS

## 8340 SMART IP-DECT AP INTEGRATED ANTENNAS 8340-C SMART IP-DECT AP INTEGRATED ANTENNAS AND 8340 SMART IP-DECT AP EXTERNAL ANTENNAS

The Alcatel-Lucent 8340 Smart IP-DECT Access Points (APs) product family provides DECT connectivity on OpenTouch® Suite for MLE and for small and medium business (SMB), to offer cost-effective, on-site mobility using IP network connectivity. In conjunction with Alcatel-Lucent 8212, 8232, 8242, 8262, 8262EX\* DECT handsets, the 8340 Smart IP-DECT APs offer reliable voice communications and full integration to provide seamless feature transition between Alcatel-Lucent fixed desk phones and on-site mobility.

The 8340-C Smart IP-DECT AP integrated antenna takes benefit of all the features of the 8340 Smart IP-DECT integrated antennas except the support of G729AB Voice audio codec.

The Alcatel-Lucent 8340 IP-DECT is HD-voice ready according to CAT-iq and will protect your investment when end to end high audio quality will be available and is compatible with existing 4080 IP-DECT installations.



**8340 Smart IP-DECT AP Integrated Antennas**  
**3BN67188AA**

**8340-C Smart IP-DECT AP integrated antennas**  
**3BN67190AA**



**8340 Smart IP-DECT AP External Antennas**  
**in outdoor box**  
**3BN67189AA+3BN67184AA+3BN67185AA**

### KEY FEATURES

- Support Alcatel-Lucent telephony protocol: AGAP
- Support GAP protocol
- Support identity, authentication and encryption as defined in ETSI
- Radio coverage from 50 m to 300 m (approximately 55 yd to 328 yd) depending on location and environment
- Switched antenna diversity
- Products for all frequency bands: Europe, US (DECT 6.0), South America and Asia
- Adapted for indoor and outdoor environments
- Integrated antennas
- SMA connectors for external antennas on indoor and outdoor models

### KEY BENEFITS

- Provide cost-effective on-site mobility in IP-only and IP/TDM networks
- Offer end users access to OmniPCX® Enterprise call server voice features
- Adapted for all enterprise environments: office and industrial
- Suitable for mid-sized and large enterprises as well as branch offices
- Coverage can fit most difficult areas using external antennas
  - Support 8232 DECT handsets in AGAP mode 8212, 8232, 8242, 8262, 8262EX\* in GAP mode on OmniPCX Enterprise
  - Support 8212, 8232, 8242 in GAP mode on OXO Connect with corporate directory and messaging
  - HD-voice ready according to CAT-iq
  - Compatible with 4080 IP-DECT existing installations

\* Available in 2017

## TECHNICAL SPECIFICATIONS

### Radio specifications

- DECT/GAP
- Frequency band
  - Europe: 1.88 GHz – 1.90 GHz
  - US: 1.92 GHz – 1.93 GHz
  - South America: 1.91 GHz – 1.93 GHz except Brazil 1910-1920 Mhz
  - Asia: 1.90 GHz – 1.906 GHz

### Functionality

- Channels can be disabled by DECT AP (DAP) manager to adapt to local regulations
- Channel bandwidth: 1.728 MHz
- Transmission carriers: 10
- Maximum number of simultaneous active calls: 11
- Over the air synchronization; requires one channel
- RF power 250 mW, limited to 100 mW for US (DECT 6.0)
- Sensitivity: Typical -90 dBm measured at antenna connection at BER=0.001
- Radio coverage from 50 m to 300 m (approximately 55 yd to 328 yd) depending on location and environment
- Switched antenna diversity
- Integrated omni-directional antenna 3dBi gain (maximum)
- SMA connectors for connecting external antennas
- SAR: < 0.283 W/kg for 11 simultaneous active calls

### DECT protocol specifications

- ETSI GAP compliant
- Alcatel-Lucent AGAP protocol
- Support identity, authentication and encryption
- Audio CODEC G726
- OmniPCX Enterprise configuration: up to 256 access points per system; 750 access points with Premium Customer Support process, 1500 DECT handsets
- OXO Connect or OmniPCX Office RCE configuration: up to 16 access points and 50 DECT handsets

\* Not available on 8340-C Smart IP-DECT AP integrated antennas

### IP specifications

- IPV4
- DHCP/TFTP, DHCP option 12
- Multicast RFC1112: multicast-aware routers
- QoS: IEEE 802.1 P/Q
- Audio CODEC: G711 (A,μ), G729AB \*
- Framing: 20 ms, 30 ms, 40 ms, 50 ms or 60 ms
- Manufacturing & customer certificates support readiness

### Electrical interface

- IP interface 10/100Base-T, IEEE802.3
- IPV4
- RJ45 connector
- Cabling CAT5 or CAT 6 UTP

### Power feeding

- Remote power feeding on IP link 802.3af
- PoE class 2 (6.49 W maximum)
- Local power feeding for extended wiring range to call server must comply with clause 2.5 (limited power source) per CSA/UL/IEC/EN60950-1
- Uses same PoE injector as the Alcatel-Lucent OmniTouch<sup>®</sup> 8082 My Instant Communicator (IC) Phone

### Operating temperature

- Indoor: 23°F to 113°F (-5°C to 45°C)
- Outdoor: 32°F to 113°F (-20°C to +45°C)

### Dimensions

#### (Wall and ceiling mountable)

#### Indoor

- Height: 6.85 in. (174 mm)
- Width: 5.7 in. (145 mm)
- Depth: 1.69 in. (43 mm)
- Weight: 11.29 oz. (320 g)

#### Outdoor

- Height: 9.45 in. (240 mm)
- Width: 11.42 in. (290 mm)
- Depth: 3.46 in. (88 mm)
- Weight: 43.39 oz. (1.23 kg)

### Serviceability

- LED status indication
- Software downloading from DAP manager
- Web-based management tools
  - Internet Explorer 6 or higher
  - Firefox

### DAP manager platforms

- Microsoft Windows XP Professional, SP2/SP3 32 bits
- Windows 7 Professional/ Enterprise/ Ultimate 32/64 bits
- Windows 8 32/64 bits editions
- Windows Server 2003 SP2 32 bits
- Windows 8.1 32/64 bits editions
- Windows Server 2003 R2 SP2 32 bits
- Windows Server 2008 SP2 32/64 bits
- Windows Server 2008 R2 SP2 64 bits
- Windows 2012 64 bits server (Windows 8 server)
- Windows 2012 R2 64 bits (Windows 8 server)

### DAP manager hardware requirements

- At least 2.6 GHz CPU speed
- Minimum 1-Gb RAM
- CD-ROM drive
- Minimum 1-Gb hard disk space

### DAP manager software requirements

- Windows Internet Information Services (IIS)

### Regulatory

#### EU directives

- R&TTE 1999/5/EC
- EMC 2004/108/EC
- LVD 2006/95/EC
- ROHS 2011/65/EU
- WEEE 2012/19/EC
- Eco design 2009/125/EC

#### Safety

- IEC 60950-1
- EN 60950-1
- UL 60950-1
- CAN/CSA-22.2 No 60950-1

#### EMC and radio

- EN 301 406
- EN 301 489-01
- EN 301 489-06
- IEC 61000-4-2 Level 3 criteria B
- IEC 61000-4-3 Level 3 criteria A (3V/m except in GSM frequency range: 10V/m)
- FCC CFR47 Part 15D
- RSS 213
- Anatel (6kV contact discharge and 8 kV air discharge)

## **SAR**

- EN 50385
- FCC OET Bulletin 65
- IEEE 1528
- RSS-102

## **DECT**

- EN 300 175
- EN 301 406 (TBR6)
- EN 301 176-2 (TBR10)

## **Environmental**

- ETS
  - Operation (indoor):  
ETSI EN 300 019-1-3-class 3.2
  - Operation (outdoor):  
ETSI EN 300 019-1-4- class 4.1 with  
-20°C for low temperature & +45°C as  
high temperature
  - Storage :  
ETSI EN 300 019-1-1- class 1.2
  - Transport:  
ETSI EN 300-019-1-2-class 2.3
- IP Class
  - IP Class (IEC 60529)
  - Indoor base station: IP40
  - Outdoor base station: IP66

## **Accessories**

- 3BN67184AA outdoor box
- 3BN67185AA 8 dBi Gain antenna
- 3MG27035xx PoE injector
- 3BD52212AA 7,5 dB Gain antenna  
(requires 3DC01001AA)
- 3DC01001AA DC blocking module
- 3BD52205AA 8dB right circular antenna
- 3BD52206AA 8dB left circular antenna

### **enterprise.alcatel-lucent.com**

Alcatel-Lucent and the Alcatel-Lucent Enterprise logo are trademarks of Alcatel-Lucent. To view other trademarks used by affiliated companies of ALE Holding, visit: [enterprise.alcatel-lucent.com/trademarks](http://enterprise.alcatel-lucent.com/trademarks). All other trademarks are the property of their respective owners. The information presented is subject to change without notice. Neither ALE Holding nor any of its affiliates assumes any responsibility for inaccuracies contained herein. (September 2016)