

Alcatel-Lucent OmniAccess AP175 Access Points

DUAL RADIO MIMO OUTDOOR ACCESS POINT

The multifunction AP-175 is an affordable, fully hardened outdoor 802.11n access point (AP) that provides maximum deployment flexibility in high-density campuses, storage yards, warehouses, container/transportation facilities, extreme industrial production areas and other harsh environments. The high-performance AP-175 delivers wire-like performance at data rates up to 300Mbps per radio.



Overview

Alcatel-Lucent OmniAccess The AP-175 features two 2x2 MIMO dual-band 2.4-GHz/5-GHz radios with quad antenna interfaces. Each radio is capable of providing a maximum aggregate transmit power of up to 25dBm. With wall and mast mounting options, the AP-175 is built to provide years of trouble-free operation.

Engineered to survive in harsh outdoor environments, the AP-175 withstands exposure to high and low temperatures, persistent moisture and precipitation, and is fully sealed for protection from airborne contaminants. All electrical interfaces include industrial-strength surge protection.

As an 802.11n AP, the AP-175 works with Alcatel-Lucent's centralized WLAN Switch/Controllers to enable the use of wireless as a primary connection with speed and reliability comparable to a wired LAN. It also increases performance by utilizing techniques such as channel bonding, block acknowledgement and MIMO radios.

Advanced antenna technology also increases range and reliability. The key to ensuring wire-like performance and reliability is Alcatel-Lucent's unique Adaptive Radio Management (ARM) and spectrum analysis capabilities, which manage the 2.4-GHz and 5-GHz radio bands to mitigate RF interference and maximize Wi-Fi client performance.

The multifunction AP-175 can be configured through the Alcatel-Lucent WLAN Switch/Controller to provide wireless LAN access with part-time air monitoring, dedicated air monitoring for wireless IPS and spectrum analysis, Remote AP (RAP) functionality or secure enterprise mesh.

The AP-175 can operate either from standard 802.3at power-over-Ethernet (PoE+) sources (AP-175POE model), a 100-240 volt AC power source (AP-175AC model), or a 12-48 volt DC power supply or solar and plant bus power sources. The AC and DC powered models provide an 802.3af PoE power source (PSE) on the Ethernet interface.

FEATURES	BENEFITS
Dual high-powered radios with high performance	Multi-service 802.11a/b/g/n WLAN. High-performance secure enterprise mesh and LAN bridging across the 2.4 to 2.5 GHz and 5 GHz RF spectrums. Dual-band concurrent 802.11a/n plus b/g/n, delivering data rates up to 300 Mb/s per radio.
Flexible power options	Choose from a standard 802.3 at power-over-Ethernet (PoE+) sources (Model OAW-AP175POE), a 100- 240 volt AC power source (Model OAW-AP175AC), or a 12-48 volt DC power supply or solar and plant bus power sources (Model OAW-AP175DC).
Advanced wireless network functions	WLAN access, RAP functionality, mobility services delivery, air monitoring/wireless intrusion detection and prevention, spectrum analysis and RF management.
Flexible mounting options	Wall, pole or mast mounting options.
Rugged construction	Outdoor rated construction with the capability to function in extreme high or low temperatures. Enclosure is sealed to protect against moisture and airborne contaminants.

Technical specifications

Application

- 802.11n outdoor AP provides maximum deployment flexibility in high-density campuses, storage yards, warehouses, container/ transportation facilities, extreme industrial production areas and other harsh environments

Operating mode

- 802.11a/b/g/n AP, air monitor (AM) and Remote AP (RAP)
- Spectrum monitor, AM and RAP
- AM and RAP
- RAP
- Secure enterprise mesh

Radios

- Software-configurable dual radio capable of supporting 2.4 GHz and 5 GHz
- 802.11n capable, implementing 2x2 MIMO with two spatial streams, providing up to 300 Mbps data rate per radio
- Maximum (aggregate) transmit power per radio: 25dBm

RF management

- Automatic transmit-power and channel-management control with auto coverage-hole correction via Adaptive Radio Management (ARM)

- Spectrum analysis remotely scans the 2.4-GHz and 5-GHz radio bands to identify sources of RF interference. This provides visibility into non-802.11 RF interference sources and their effect on 802.11 channel quality.

Advanced features

- Integrated RAP, secure enterprise mesh point or portal, wireless intrusion detection and prevention

Power

- OAW-AP175POE: 48-volt DC 802.3at power over Ethernet (PoE+)
- OAW-AP175AC: 100-240 volt AC from external AC power source
- OAW-AP175DC: 12-48 volt DC from external DC power source
- Maximum power consumption: 18 watts (excludes power consumed by any PoE device connected to and powered by the AP-175AC or AP-175DC)

Power out

- The AC and DC powered models provide an 802.3af PoE power source (PSE) on the Ethernet interface

Wireless radio specifications

- AP type: Dual-radio, dual-band 802.11n outdoor
- Supported frequency bands (country-specific restrictions apply):
 - 2.400 to 2.4835 GHz
 - 5.150 to 5.250 GHz
 - 5.250 to 5.350 GHz
 - 5.470 to 5.725 GHz
 - 5.725 to 5.850 GHz
- Available channels: WLAN Switch/Controller- managed, dependent upon configured regulatory domain
- Supported radio technologies:
 - 802.11b: Direct-sequence spread-spectrum (DSSS)
 - 802.11a/g/n: Orthogonal frequency division multiplexing (OFDM)
 - 802.11n: 2x2 MIMO with two spatial streams
- Supported modulation types:
 - 802.11b: BPSK, QPSK, CCK
 - 802.11a/g/n: BPSK, QPSK, 16-QAM, 64-QAM
- Transmit power: Configurable in increments of 0.5 dBm

- Maximum transmit power:
 - 2.4 GHz: 25 dBm (limited by local regulatory requirements)
 - 5 GHz: 25 dBm (limited by local regulatory requirements)
- Maximum ratio combining (MRC) for improved receiver performance
- Association rates (Mbps):
 - 802.11b: 1, 2, 5.5, 11
 - 802.11a/g: 6, 9, 12, 18, 24, 36, 48, 54
 - 802.11n: MCS0 - MCS15 (6.5 Mbps to 300 Mbps)
- 802.11n high-throughput (HT) support: HT 20/40
- 802.11n packet aggregation: A-MPDU, A-MSDU

Antenna

- Quad, N-type female interfaces (2 x 2.4 GHz, 2 x 5 GHz) for external antenna support (supports MIMO)
- Feeder cable may be used for external antenna deployments

Mounting

- Wall or mast mounted using the mounting bracket supplied with the unit; solar shield included

Interfaces

Network

- 1 x 10/100/1000BASE-T Ethernet (RJ-45), auto-sensing link speed and MDI/MDX

Power

- 1 x DC power connector (in OAW-AP175DC model only)
- 1 x AC power connector (in OAW-AP175AC model only)

Antenna

- 4 x N-Type female antenna interfaces

Other

- 1 x USB console interface

Mechanical

- Dimensions (unit)
 - 260 mm x 240 mm x 105 mm (10.2" x 9.4" x 4.1")
 - Shipping box: 395mm x 348mm x 375mm (15.6" x 13.7" x 14.8")
- Weight (AP175POE):
 - Unit: 3.5kg (7.7lb)
 - Shipping box: 8.25kg (18.2lb)
- Weight (AP175AC & AP175DC):
 - Unit: 4.25kg (9.4lb)
 - Shipping box: 9kg (19.8lb)

Certifications

- Wi-Fi certified: 802.11a/b/g/n

Warranty

- One year warranty.

Minimum AOS version

- 5.0.2.1

Environmental

- Operating:
 - Temperature: -30°C to +60°C (-22°F to +140°F) for POE powered models; -40° C to 55° C (-40° F to 131° F) for AC and DC powered models
 - Relative humidity: 5% to 95% non-condensing
 - Altitude: Up to 3,000 meters (9,850 feet)
- Storage and transportation temperature range:
 - -40°C to +70°C (-40°F to +158°F)
 - Weather rating: IP66
 - Wind survivability: Up to 165 mph
 - Shock and vibration: ETSI 300-19-2-4 spec T41.E class 4M3
 - Transportation: ISTA 2A

Regulatory

- FCC/Industry of Canada
- R&TTE Directive 1995/5/EC
- EN 300 328
- EN 301 893
- CB Scheme Safety, cTUVus
- Korea KCC
- Mexico NOM/COFETEL
- IEC 60529 IP66, NEMA 4X
- ATEX Zone 2
- CE Marked
- Low Voltage Directive 72/23/EEC
- EN 301 489
- UL/IEC/EN 60950
- Japan MIC/VCCI
- Brazil ANATEL
- China SRRC/CCC
- AS/NZS 4260, 4771, 3548

For more country-specific regulatory information, and approvals, please see your Alcatel-Lucent representative.

Ordering Information

PART NUMBER	DESCRIPTION
OAW-AP175POE	Outdoor access point designed for high-density applications. Supports 802.11a/n and 802.11b/g/n dual-radio (320mW). 2x2 MIMO with two spatial streams, providing up to 300 Mbps data rate per radio. Supports one 10/100 Base-T (RJ-45) Ethernet interface supporting 48-volt DC 802.3at power over Ethernet (PoE+). 4 N-type female interfaces (2 x 2.4 GHz, 2 x 5 GHz) for external antenna support. Wall or poll mounted
OAW-AP175AC	Outdoor access point designed for high-density applications. Supports 802.11a/n and 802.11b/g/n dual-radio (320mW). 2x2 MIMO with two spatial streams, providing up to 300 Mbps data rate per radio. Supports one 10/100 Base-T (RJ-45) Ethernet interface. Requires 100-240 volt AC from external AC power source. 4 N-type female interfaces (2 x 2.4 GHz, 2 x 5 GHz) for external antenna support. Wall or poll mounted
OAW-AP175DC	Outdoor access point designed for high-density applications. Supports 802.11a/n and 802.11b/g/n dual-radio (320mW). 2x2 MIMO with two spatial streams, providing up to 300 Mbps data rate per radio. Supports one 10/100 Base-T (RJ-45) Ethernet interface. Requires 12-48 volt DC from external DC power source. 4 N-type female interfaces (2 x 2.4 GHz, 2 x 5 GHz) for external antenna support. Wall or poll mounted using the mounting bracket supplied with the unit; solar shield included.
OAW-AINS2KKIT00	OmniAccess AP175 installation kit
OAW-ACONGEUSB00	1.5m USB-DB9 console cable
OAW-AETHGEL0500	5m shielded Ethernet cable with RJ-45 connectors
OAW-AP-LAR-1	Outdoor Antenna Lightning Arrestor. Lightning Surge Arrestor for the OAW-AP80/AP85/AP175 Access Points: Single, In-line lightening arrester with N-type Male to N-type Female interface. Supports RF frequency pass through of 2 – 6 GHz.
OAW-AP-CBL-1	Outdoor Antenna Cable Extension. 10 ft long low-loss LMR 400 antenna extension cable for use with the OAW-AP80 Outdoor Access Points, interfaces OAW-AP80/AP85/AP175 N-Type Female interface to N-Type Male on antenna.
AP-ANT-80 to AP-ANT-90 and other outdoor antenna options	Detachable Antennas

RF performance Table

	Max TX Power per Active TXchain (dbm)	RX sensitivity (dbm)	Max TX Power per Active TXchain (dbm)	RX sensitivity (dbm)
	2.4 GHz		5 GHz	
802.11b				
1 Mbps	20	-96		
2 Mbps	20	-96		
5.5 Mbps	20	-94		
11 Mbps	20	-93		
802.11a/g				
6 Mbps	20	-96	22	-97
9 Mbps	20	-96	22	-96
12 Mbps	20	-96	22	-96
18 Mbps	20	-95	22	-94
24 Mbps	19	-92	22	-88
36 Mbps	18	-89	20	-86
48 Mbps	17	-85	19	-82
54 Mbps	17	-83	18	-80
802.11n HT20				
MCS0	22	-94	21	-97
MCS1	22	-93	20	-94
MCS2	22	-92	19	-91
MCS3	22	-89	18	-87
MCS4	21	-85	17	-86
MCS5	20	-81	16	-81
MCS6	19	-80	15	-79
MCS7	18	-78	15	-77
MCS8	22	-94	21	-97
MCS9	22	-93	20	-94
MCS10	22	-92	19	-91
MCS11	22	-89	18	-87
MCS12	21	-85	17	-86
MCS13	20	-81	16	-81
MCS14	19	-80	15	-79
MCS15	18	-78	15	-77
802.11n HT40				
MCS0	21	-92	19	-92
MCS1	21	-91	19	-90
MCS2	21	-89	18	-88
MCS3	20	-86	17	-85
MCS4	19	-83	16	-83
MCS5	18	-79	15	-79
MCS6	18	-77	14	-77
MCS7	17	-75	14	-73
MCS8	21	-92	19	-92
MCS9	21	-91	19	-90
MCS10	21	-89	18	-88
MCS11	20	-86	17	-85
MCS12	19	-83	16	-83
MCS13	18	-79	15	-79
MCS14	18	-77	14	-77
MCS15	17	-75	14	-73

Maximum capability of the hardware provided. Maximum transmit power will be limited by local regulatory settings.

www.alcatel-lucent.com Alcatel, Lucent, Alcatel-Lucent and the Alcatel-Lucent logo are trademarks of Alcatel-Lucent. All other trademarks are the property of their respective owners. The information presented is subject to change without notice. Alcatel-Lucent assumes no responsibility for inaccuracies contained herein. Copyright © 2012 Alcatel-Lucent. All rights reserved.

