

# ALCATEL-LUCENT OMNITOUCH 8118/8128 WLAN HANDSETS

The Alcatel-Lucent OmniTouch® 8118/8128 wireless LAN (WLAN) handsets provide a convenient and practical solution for any business environment. Both handsets are equipped with IEEE 802.11a/b/g standard radio support so that businesses can choose the Wi-Fi implementation that best addresses their need for application segmentation, interference mitigation and user density. The Alcatel-Lucent OmniTouch 8118 WLAN handset meets most office mobility needs. The Alcatel-Lucent OmniTouch 8128 WLAN handset extends the capabilities of the OmniTouch 8118 WLAN handset to include a color display, hands-free, Ekahau Real Time Location System (RTLS) support and push-to-talk capabilities for workgroup communications on Alcatel-Lucent communications servers.



**OmniTouch 8118**



**OmniTouch 8128**

## FEATURES

- Supports Alcatel-Lucent telephony protocol
- Supports 802.11a/b/g radio
- Leverages the Wireless LAN for voice and data applications
- Delivers high voice quality using standardized 802.11 quality of service (QoS) on OmniAccess® WLAN infrastructures
- Supports seamless handover based on the OmniAccess WLAN infrastructures
- Provides direct access to dial-by-name and speakerphone functions
- Supports over-the-air software upgrades
- Supports quick phone parameter configuration through the USB configuration cradle station

## BENEFITS

- Infrastructure investment protection (compatible with 802.11a/b/g radio networks and WLAN infrastructure standards)
- Delivers business telephony features throughout the workplace, contributing to improved end-user responsiveness and productivity
- Interchangeable battery units to support the most demanding enterprise usage requirements
- Enhanced durability (shock, vibration, liquid and dust resistance)
- Support for both existing Alcatel-Lucent 300/600 WLAN handsets and 310/610 WLAN handsets on existing infrastructures
- Support for wireless security: Wi-Fi Protected Access (WPA and WPA2) and Wireless Encryption Protocol (WEP)
- Enhanced design, soft case painting for 8128
- Increased autonomy: Up to 15 hours talk time
- Integration with OTNS Ecosystem

## TECHNICAL SPECIFICATIONS

### Mechanical characteristics

- Dimensions: (height x width x depth) 5.27 in. x 2.08 in. x 1.02 in. (134 mm x 53 mm x 26 mm)
- Weight: 4.8 oz (36 g)
- Color:
  - OT8118: Black/silver
  - OT8128: Black, soft paint
- Graphic display:
  - OT8118: Monochrome, 112 pixels x 115 pixels
  - OT8128: 65K Colors, 176 pixels x 220 pixels
- Display backlight
- Keypad backlight on OT8128
- Hands-free on OT8128
- Vibrator
- Headset connector 2.5 mm
- LED for status indication
- Profile key:
  - OT8118: 4 defined profiles
  - OT8128: 10 configurable profiles
- Push to Talk: OT8128 and OmniPCX® Enterprise required
- Ring tones: 6 user selectable with 8-step volume control
- Screensaver: OT8128 – Customizable
- Handset MMI languages: English U.S., French, German, Spanish, Italian, Dutch, Swedish, Danish, Norwegian, Finnish, Portuguese, Polish, Flemish, Czech, Greek, Hungarian, Turkish, Russian, 1 additional downloadable
- System languages: Communication server dependant

### Battery pack

- Li-Polymer
- Talk time: Up to 15 hours
- Standby time: Up to 100 hours
- Charging time: 2.5 hours
- Charge/discharge cycles: ≥ 80% capacity after 400 cycles

### Radio specifications

- WLAN
- Wireless standard: IEEE 802.11a/b/g
- Frequency range:
  - 2.4 GHz to 2.4835 GHz ('b' and 'g')
  - 5.15 GHz to 5.35 GHz and 5.725 GHz to 5.85 GHz ('a' in North America)
  - 5.15 GHz to 5.35 GHz and 5.47 GHz to 5.725 GHz ('a' in Europe)
- Radio frequency output power:
  - Dynamic according to 802.11h

- Adjustable through configuration
- Up to 100 mW/20 dBm

### Protocol specifications

- Alcatel-Lucent communication servers (NOE)

### Quality of service

- Standardized:
  - 802.11e, WMM (EDCA)
  - WMM Power Save (U-APSD)
  - Call admission control: TSPEC, WMM AC
- Cisco CCXv2

### Roaming enhancement

- PMK caching
- OKC (opportunistic key caching)
- CCKM (Cisco)

### Audio codecs

- ITU-T G.711 (A and μ law) G729AB

### IP address assignment

- Static, DHCP

### DSCP

- PBX or local settings

### TFTP

- Yes
- SUOTA (software update over the air)

### Wireless security

- 802.11i
- WEP 64 and 128 bits
- WPA/PSK and WPA2/PSK
- Cisco FSR

### Authentication

- PEAP-MSCHAPV2
- EAP-TLS
- EAP-FAST
- Radius servers: Microsoft IAS, Steel-Belted, Free Radius

### Certificates

- Factory
- Up to 4 root and clients

### Registration

- Up to 4 systems
- Manual selection

### WLAN infrastructures

- Alcatel-Lucent: AP, IAP

- Aruba
- Cisco
- Meru, Trapeze, Motorola (supported within Premium Customer support process). Refer to PCS documents for availability

### Location

- OT8128: Ekahau RTLS

### Notifications

- OpenTouch Notification Service Integration (OTNS): notifications, loudspeaker announcement, alarm call, panic button

### Environmental

- Operating temperature: -5°C to +45°C (23°F to 113°F)
- Storage temperature: -25°C to +55°C (-13°F to +131°F)
- IP Class: IP44, IEC 60529

### Serviceability

- Site survey tool
- Diagnostic mode
- Syslog mode
- Software upgrade through TFTP

### Configuration tool

- USB configuration cradle station
- WinPDM (Windows portable device manager)
- Central management IMS3

### Regulatory

- EC Directive:
  - 1999/5/EC (R&TTE)
  - 2009/125/EC (Eco Design)
- Safety:
  - IEC 60950-1
  - EN 60950-1
  - UL 60950-1
  - CAN/CSA-22.2 No. 60950-1
- EMC and radio:
  - EN 300 328
  - EN 301 893
  - EN 301 498-1
  - EN 301 498-17
  - IEC/EN 61000-4-2 Level 3 Criteria B
  - IEC/EN 61000-4-3 Level 3 Criteria A
  - FCC 47CFR Part 15 Subpart B
  - FCC 47CFR Part 15 Subpart C
  - FCC 47CFR Part 15 Subpart E
  - RSS-210 Annex 8
- SAR:
  - EN 50385

- FCC OET Bulletin 65, Supplement C
- RSS-102 Issue 3
- Normal operation: 1.3 W/kg
- Body worn operation: 1.16 W/kg
- Hearing aid: 47CFR Part 68

### **Accessories**

- Desktop charger, 3 models:
  - 3BN78403AA Europe
  - 3BN78403AB US-UK-AUS
  - 3BN78403AC without PSU for countries not supporting above plugs
- 3BN78404AA Standard battery
- 3BN78406AA Rack charger
- 3BN78407AA Battery rack charger
- 3BN78408AA Leather carrying case
- 3BN78409AA Belt clip
- 3BN78410AA Swivel clip
- 3BN78414AA Configuration cradle station
- 3BN78415XX Central management IMS3 Gateway

#### **[enterprise.alcatel-lucent.com](http://enterprise.alcatel-lucent.com)**

Alcatel-Lucent and the Alcatel-Lucent Enterprise logo are trademarks of Alcatel-Lucent. To view other trademarks used by affiliated companies of ALE Holding, visit: [enterprise.alcatel-lucent.com/trademarks](http://enterprise.alcatel-lucent.com/trademarks). All other trademarks are the property of their respective owners. The information presented is subject to change without notice. Neither ALE Holding nor any of its affiliates assumes any responsibility for inaccuracies contained herein. (December 2016)